

PRELIMINARY

DATA SHEET

Subject to Change



Shown with optional high-g lens mount.

Miro Airborne HD

Shipments start in October 2010

Your Ideal Solution for
High Resolution
Airborne Applications

Key Benefits:

WHEN IT'S TOO FAST TO SEE, AND TOO IMPORTANT NOT TO®

Compact. Lightweight. Rugged. The perfect balance of resolution, speed, and light-sensitivity. Flexible triggering. Secure, removable, non-volatile CompactFlash® memory. Everything you need in a high-speed digital imaging system for airborne applications.

With a variety of image sizes up to 1920 x 1080 and a maximum full-resolution frame rate of **320 frames-per-second** (fps), you will find a setting that matches your need. (Maximum frame rates at reduced resolutions are as high as 28,000 fps!)

The Phantom Miro Airborne HD's custom-designed CMOS sensor has an ISO 12232 rating of 640 (monochrome) ensuring the **light-sensitivity** required in high-speed imaging applications. And, it comes in color or monochrome versions. With access to all 10-bits of grayscale information, you can bring out the detail in shadows that result from uncontrollable and constantly changing lighting situations.

With shutter speeds as low as 10 microseconds, you can **freeze objects in motion**, eliminate blur, and bring out the detail you need for successful motion analysis.

Key Features:

Resolution (Pixels): 1920 x 1080

HD Resolution under 1" (1920 x 1080) and
2/3" (1280 x 720) C-mount Lenses

No CSR Required

Frames-per-second (fps) at full resolution: 320

Maximum Frame Rate: 28,000 fps at 1920 x 8

Exposure Time (shutter speed): 10µs to 1/frame-rate

Built in Memory: 2 GB, 4 GB option

ISO (ISO-12232 Standard): 640 monochrome

Non-volatile Memory: Removable CompactFlash

Memory Segmentation: 1 to 4

Pixel Bit-depth: 10-bits

Camera Trigger and Signals:

- Trigger (TTL or +28VDC)
- Aux (IRIG-out or Strobe)
- Ready
- FSync
- IRIG-in
- Video (NTSC/PAL)

10/100 Ethernet

Miro Airborne HD



Features like Auto Exposure help deal with subjects moving from sunlight to shadow

Connect your Phantom Miro Airborne HD camera to a PC using 10/100 Ethernet for camera programming and control and to retrieve your test images in our efficient cine format for later analysis and processing. Set up the camera with the Phantom Software, and those settings will be retained, even after power down. You can then deploy the camera untethered from the PC if you choose.

The Miro Airborne HD camera has **two types of memory**: volatile for high-speed image capture, and removable CompactFlash non-volatile memory. After the camera is triggered, the captured

images can automatically be copied to the non-volatile memory for safe storage. If the mission requires multiple stores releases or has the possibility of false triggers, the camera can be automatically rearmed for the next trigger, and the process repeats.

Using the Phantom Software you can **save slow-motion movies in popular formats** such as QuickTime or AVI, or you can save frames as JPEG or TIFF images. Easily email movies or frames to colleagues.

Take advantage of our **flexible triggering**. When you power-up the camera, it begins taking images at the programmed settings and stores them in a circular buffer in internal memory. Set up the camera so that a trigger (from external hardware or software on a connected PC) starts your recording, stops your recording, or records a selectable number of frames before and after the trigger.

The Phantom Miro Airborne HD can be connected to a standard analog video monitor (PAL or NTSC) for real-time monitoring of the camera image or for playback of images stored in the camera's memory. This provides a great way to check camera status prior to a mission. Camera live video can even be fed into the aircraft's telemetry system for ground station monitoring.

Lens mounting holes provide anchorage for additional lens support and flange mount High-g and vibration resistant lenses. Mounting plates with standard 1/4-20 holes on two sides of the camera give you plenty of mounting options. Or, you can remove these plates and replace them with custom plates that meet your specific requirements.

The Miro Airborne HD camera has passed the following qualification tests

	Miro Airborne Test Conditions	Test Method
Operating Temperature	-30°C to +50°C	Mil-Std-810G Method 502.5, Proc III Mil-Std-810G Method 501.5, Proc II-III
Storage Temperature	-50°C to +70°C	Mil-Std-810G Method 502.5, Proc I Mil-Std-810G Method 501.5, Proc I
Altitude, Operating	Sea level to 40,000 feet	Mil-Std-810G Method 500.0, Proc III
Altitude, Non-operating	-500 to 50,000 feet	Mil-Std-810G Method 500.0, Proc III
Humidity	95% non-condensing	Mil-Std-810G Method 507.5, Proc I, II
Random Vibration	Functional: 0.20g ² /Hz for 1 hour in each of the three orthogonal axes Endurance: 0.83g ² /Hz for 1 hour in each of the three orthogonal axes	Mil-Std-810G Method 514.6, Proc I
EMI/RFI	Passed	EN-55033A, IEC-61000-3-2 and 3-3, EN-55024, EN-50082, IEC-61000-4-2
Acceleration	6g for 1 minute on all axes	RTCA/DO-160E Section 7.3.3 Crash Safety Sustained
Shock	40g, 10ms in all three axes, saw tooth	Mil-Std-810G Method 516.6, Proc I, III
Magnetic Field Immunity	500A/m	Mil-Std-1399-70-1
Regulatory	Passed	EN-60950-1, UL-60950-1
ESD	8kV air discharge	IEC-61000-4-2

Resolution/Speed Chart

H	V	FPS*
1920	1080	320
1920	1024	338
1920	800	434
1280	1080	320
1280	800	434
1280	720	482
1280	600	578
1280	512	678

* Preliminary Specifications, subject to change

When recording at 1920 pixels of horizontal resolution, record time into 4 GB of memory is 4.85 seconds. When recording at 1280 pixels of horizontal resolution, record time into 4 GB of memory is 7.7 seconds.



PRELIMINARY

DATA SHEET

Miro Airborne HD

Additional Features:

Analog video out: PAL & NTSC

Lensing: 1-inch and 2/3-inch C-mount

Size (without lens): 11 x 6.5 x 8 cm (W x D x H)
4.3 x 2.56 x 3.15 in

Weight (without lens): 2 lbs (0.9 kg)

Standard Accessories:

- AC power supply with power cord
- 8 GB CompactFlash card
- Capture cable with 5 BNCs - 18"
- Ethernet cable - 5m
- Single-user software license
- Software CD

External Power: 15-30 VDC, 9W

The Miro Airborne HD is a **High-g camera**, ensuring you will get great pictures, even when subjected to 40gs of shock. All internal electrical components are conformally coated to protect against damp/humid environments and condensation.

IRIG-B input gives you a GPS-derived time reference input to the camera. This allows you to time stamp each image if running asynchronous to IRIG timing. Or, phase-locking to IRIG allows frame synchronization to the GPS timing at **key frame rates such as 100, 200, and 400 fps**. This permits synchronization of the camera to a time standard or to other cameras without additional wiring.

Focused

Since 1950, Vision Research has been shooting, designing, and manufacturing high-speed cameras. Our single focus is to invent, build, and support the most advanced cameras possible.

VISION
RESEARCH

An **AMETEK** Company

100 Dey Road
Wayne, NJ 07470 USA
+1.973.696.4500
phantom@visionresearch.com

www.visionresearch.com

All specifications are subject to change without notice. Rev June 2010

AMETEK Vision Research's digital high-speed cameras are subject to the export licensing jurisdiction of the Export Administration Regulations. As a result, the export, transfer, or re-export of these cameras to a country embargoed by the United States is strictly prohibited. Likewise, it is prohibited under the Export Administration Regulations to export, transfer, or re-export AMETEK Vision Research's digital high-speed cameras to certain buyers and/or end users.

Customers are also advised that some models of AMETEK Vision Research's digital high-speed cameras may require a license from the U.S. Department of Commerce to be: (1) exported from the United States; (2) transferred to a foreign person in the United States; or (3) re-exported to a third country. Interested parties should contact the U.S. Department of Commerce to determine if an export or a re-export license is required for their specific transaction.