

Tumble Tester II



Class of its own

Heinä's Tumble Tester II is used to test the breakage of various small items and components. This machine can be used to perform the standard tests IEC 60068-2-31 (incorporated IEC 68-2-32 and BS EN 60068-2-32).

Operating principles

The item to be tested is placed in the Tumble Tester. The desired number of falls is selected and the machine is set in motion. After this the machine will drop the item onto the base of the machine at random positions (free fall).

The rotation speed of the machine is selected in order to get the item to fall to the middle of the base. The machine can be modified according to the customer's wishes.

The Tumble Tester is conformable to the European Machine Directive 89/392 and its amendments 91/368, 93/44 and 93/68.


New features!



5.7" color display



Easy to change barrels



Barrel change system

Technical specifications

Width:	1160 mm
Height:	1600 mm
Depth:	1500 mm
Fall heights:	1000 mm and 500 mm
Fall rate, stepless adjustment:	5-15 / min
Engine power:	0,18 KW
Electrical supply:	100-240 V, 50-60 Hz
Machine weight:	200 kg
Max item weight:	1 kg
CE-marking:	Yes

Special features

- Steady aluminium frame, reliable construction
- Programmable counter
- Safe and clean design
- Safe to use: safety gate, roof, and electronic door lock
- IEC 60068-2-31 standard tumble test
- IEC 60950-1 standard tumble test
- CE certified
- Easy to operate
- Adjustable tumble rate
- Easy access to product for inspection
- Presettable drop counter, 1-9999 drops
- Inspection counter
- Service free machine
- Tester can be divided into three separate parts for easy transportation
- Five memory banks for different programs

Restrictions

Tumble Tester II must not be used to test explosive objects or such objects which at breaking release hazardous gases that may cause a health risk to the user or the surroundings